



SOP- HPC 07 Nu-Guard Anti- Graffiti Protective Coating. Fresh Surfaces.

This is a Standard Operating Procedures doc (SOP) designed to ensure the performance benefits of this protective coating deliver the expected performance outcomes.

This SOP applies to fresh murals & painted sites shortly after drying is complete.

IMPORTANT NOTE: *The amount of coating applied is crucial to best performance outcomes & has a “very rubbery feel “when dry.*

- ✓ SAFETY FIRST- eye protection as a minimum. Dish wash type gloves optional.
- ✓ Open & stir coating thoroughly. Do **not** dilute the coating.
- ✓ When **not** in use put the lid back on securely to avoid air & moisture uptake ensuring the coating is fit for ongoing use.
- ✓ The coating can be applied with a brush, roller, or spray coat. Equipment washes up with White Spirits.
- ✓ To apply the correct amount of coating needed is a tape measure, & plastic measuring jug with litre fractions, typically used for cooking.
- ✓ Measure & calculate the square metres of the surfaces to be coated.
(width x height & height x length which ever applies. – this will enable sqm calcs)
Add to get total sqm number. **Then:** divide the total sqm number by 8.
This number is the amount in litres to apply Round up the nearest 0.05l or 0.10l.
If the application number is greater than 1(litre) then the sqm number must be greater than 8 (sqm). If lower than 1(litre) then the sqm number must be less than 8(sqm)
- ✓ Apply **all** of the measured coating to the measured areas.
- ✓ Continue to apply evenly until **all** of the coating is used to achieve the target coating amount of 8.0 sqm / litre.
- ✓ Should be a single coat application but, **all** of the measured amount must be applied.
- ✓ Apply in temperatures greater than 5degrees C & Relative Humidity less than RH 85%. In other words, not very cold &/or not very damp nearly raining.
- ✓ 6hrs touch dry / 24hrs fully dry & graffiti “water washable “ready.
- ✓ The “rubbery feel” is a clear indication to the presence of the protective coating.

If you have any questions please ring Tony +64 27 448 4593 or Greg as below. We are more than happy to assist.

Greg Stevenson
Technical Director
Cleanoff Graffiti Ltd
+64 21 884 663.

CAUTION - This message may contain privileged and confidential information intended only for the use of the addressee named above. If you are not the intended recipient of this message please be notified that your use, dissemination, distribution or reproduction of this message is prohibited. If you have received this message in error please notify Cleanoff Graffiti Ltd. immediately. Much appreciated.